

DONG FENG 4x4-Tractor DF-404 EC

&lang=eng

technical data

[<< Model-overview](#)

Tractor parameters	Model:	DF-404 EC	
	Drive type:	4 WD	
	Overall dimensions LxWxH (mm):	3020 x 1588 x 2400	
	Wheel track:	Front (mm):	1100
		Rear (mm):	1280
	Wheelbase (mm):	1818	
	Ground clearance (mm):	320	
	Construction mass (kg):	1485	
	Min. Turning radius (m):	3,2	
Engine specification	Model:	4LD40B	
	Type:	4-cyl., 4-Stroke	
	Rated power (kW/PS):	29.4 / 40	
	Rated speed (rpm):	2400	
	Bore x Stroke (mm):	90 x 101	
	Total displacement (l):	2.546	

Drive system	Clutch:		double acting
	Gearbox:		(4+1) x 2
	Main drive:		Spiral bevel gear
	Differential:		Bevel gear
	Differential lock:		Jaw lock
	Final transmission (rpm):		Spur gear, External gearing
Travelling mechanism	Farm tyre	Front:	7.50 - 16
		Rear:	12.40 - 24
	Turf tyre	Front:	7.50 - 16
		Rear:	12.40 - 24
	Steering gear:		Hydraulic
	Brake:		Sealed shoe brake
Working	Hydraulic System	Lifting capacity (kg)*:	665
		3-point suspension:	Cat. I
	P.T.O Shaft	Rotating speed (rpm):	540/1.000
		Spline size:	1 3/8" Z6

* 610 mm behind lift point